




Product Name	UHMWPE FABRIC	Reference Standard/ Test Method
Product Code	U-TSHJ-003	
Width Cuttable	145cm (+2/-1cm)	ISO 22198:2006
Gram Weight	35gsm ( $\pm 5$ )	ISO 3801:1978
Fibre Composition	UHMWPE	
Colour	WHITE	
Dimensional Stability	$\leq \pm 3\%$	ISO 5077:2007 After 5 * Cleaning Cycles at 40°C
Breaking Strength (N)	Warp 1090; Fill 806	ISO 13934-1:2013
Tear Strength (N)	Warp 211; Fill 152	ISO 13937-2:2000
Formaldehyde Content (mg/kg)	Not Detectable	ISO 14184.1:2011
Bacteriostatics	Compliant	ISO 105-C06: 1994
Cleaning Recommendations		EN ISO 6330:2013, 4N 40°C

**CONTACT US AT:****SYNERTEX MATERIAL TECHNOLOGY**

Room 308, Zone 1, Building B, No. 6433, Yinggang East Road, Zhaoxiang Town, Qingpu District, Shanghai  
China, 201705

Phone: +86 21 6976 1398 Email: [info@synertexmaterial.com](mailto:info@synertexmaterial.com)

Website: [www.synertexmaterial.com](http://www.synertexmaterial.com); [www.recycledprotectivefabrics.com](http://www.recycledprotectivefabrics.com)

*All the data listed in the above table are either individual test results or the most typical indicative parameters to the best of our knowledge. Owing to existence of possible variation or deviation from case to case, the data and information shown in the table is only for your reference. However, Synertex Material Technology assumes no liability for the accuracy or completeness of the information.*