




Product Name	UHMWE UD FABRIC	Reference Standard/ Test Method
Product Code	UD-SYMT-001	
Width Cuttable	160cm (+2/-1cm)	ISO 22198:2006
Gram Weight	160gsm ( $\pm 5$ )	ISO 3801:1978
Fibre Composition	UHMWPE	
Colour	WHITE	
Dimensional Stability	$\leq \pm 3\%$	ISO 5077:2007 After 5 * Cleaning Cycles at 40°C
Breaking Strength (N)	Warp 1090; Fill 806	ISO 13934-1:2013
Tear Strength (N)	Warp 211; Fill 152	ISO 13937-2:2000
Formaldehyde Content (mg/kg)	Not Detectable	ISO 14184.1:2011
Protection level	ND IIIA,44(30 floors)	
Cleaning Recommendations		EN ISO 6330:2013, 4N 40°C

**CONTACT US AT:****SYNERTEX MATERIAL TECHNOLOGY**

Room 308, Zone 1, Building B, No. 6433, Yinggang East Road, Zhaoxiang Town, Qingpu District, Shanghai  
China,201705

Phone: +86 21 6976 1398 Email: info@synertexmaterial.com

Website: www.synertexmaterial.com; www.recycledprotectivefabrics.com

*All the data listed in the above table are either individual test results or the most typical indicative parameters to the best of our knowledge. Owing to existance of possible vairation or deviation from case to case, the data and information shown in the table is only fo your reference. However,Synertex Material Technology assumes no liability for the accuracy or completeness of the information.*